

Surface Preparation:

- Clean the surface smooth and free of moisture and debris or any kind of substance that would prevent the membrane from adhering properly.
- The roof must have a minimum slope of 1% (10mm per meter) evenly and continuously towards the drains. - Surface must be primed with **SABIT Primer D41**.at the rate 4-5m²/L Allow the primer to dry overnight

Membrane Installation:

Remove the release film by peeling back not more than 30cms at a time. Start to unroll the SSA 140 1.6mm membrane keeping the adhesive side face-down on the primed surface. Press down the membrane, working from the center to the outer edges. This will expel all trapped air, ensuring good adhesion to the primed substrate.

For subsequent rolls align the adjacent roll along the factory designed selvedge of the first roll. Re-roll the membrane. Peel back the selvedge on the initial roll, then peel back the release film or paper from the second roll and place firmly. This should be done one meter at a time. The minimum end lap should be 150mm.

If any mistake immediately removes the second roll and replace it before it reaches its full adhesion power. It is important to press again the overlaps with a light wooden roller.

SABIT SELFADO POLY SSAP 140-2 membranes should always be protected in all applications. SABIT protection boards are highly recommended as a flexible, semi hard, easy to install protection mainly before backfilling on vertical surfaces in underground tanking work. When application temperature

Drops below 10degC, it is essential to heat the primed surfaces, before applying the membrane, either with a gas torch or hot air blower. At surface temperature below 5degC, care should be taken to ensure all surfaces are dry and free of ice, frost and condensation. Material stored at temperature below 20degC should be left exposed to a warmer temperature for at least 24 hours. Ambient temperatures above 50degC may give rise to difficulty in removing the release film or paper. It will be better to wait until the temperature goes down.

PACKING

SABIT SELFADO membranes comes as standards 1x15m rolls (28 rolls per pallet). All rolls are packed vertical on pallets with special high strength shrink-wrap it must be transported and kept in stock always in a vertical position.



صنع في المملكة
العربية السعودية
مواصفات عالمية

Made in
Saudi Arabia
According to
international
standards

